

# Chapter 1

## Errata for MPI-3.0

This document was processed on September 20, 2013.

The known corrections to MPI-3.0 are listed in this document. All page and line numbers are for the official version of the MPI-3.0 document available from the MPI Forum home page at [www.mpi-forum.org](http://www.mpi-forum.org). Information on reporting mistakes in the MPI documents is also located on the MPI Forum home page.

- In all `mpi_f08` subroutine and function definitions in Chapters 3–17 and Annex A.3, in Example 5.21 on page 187 line 13, and in all `mpi_f08` `ABSTRACT INTERFACE` definitions (on page 183 line 47, page 268 lines 23 and 33, page 273 line 47, page 274 line 9, page 277 lines 12 and 21, page 344 line 22, page 346 line 12, page 347 line 36, page 475 lines 10 and 43, page 476 line 38, page 537 line 29, page 538 line 2, and page 678 line 11 through page 680 line 35), the `BIND(C)` must be removed.

Note that a previous version of this errata *added* `BIND(C)` to several declarations. Those must also be removed.

- Section 6.4.2, page 239 (`MPI_Comm_idup`) line 32 reads

```
TYPE(MPI_Comm), INTENT(OUT) :: newcomm
```

but should read

```
TYPE(MPI_Comm), INTENT(OUT), ASYNCHRONOUS :: newcomm
```

- Section 6.4.4, page 249 (`MPI_Comm_set_info`) lines 20–21 read

```
MPI_Comm_set_info(MPI_Comm comm, MPI_Info info) BIND(C)  
TYPE(MPI_Comm), INTENT(INOUT) :: comm
```

but should read

```
MPI_Comm_set_info(comm, info, ierror)  
TYPE(MPI_Comm), INTENT(IN) :: comm
```

- Section 8.1.1, page 336 (`MPI_Get_library_version`) line 17 reads

```
MPI_Get_library_version(version, resulten, ierror) BIND(C)
```

1 but should read

2 MPI\_Get\_library\_version(version, resultlen, ierror)

- 3  
4 • Section 8.1.1, page 336 (MPI\_Get\_library\_version) line 22 reads

5 MPI\_GET\_LIBRARY\_VERSION(VERSION, RESULTEN, IERROR)

6  
7 but should read

8  
9 MPI\_GET\_LIBRARY\_VERSION(VERSION, RESULTLEN, IERROR)

- 10  
11 • Section 8.2, page 339 lines 44–47, page 407 lines 47 through page 408 line 2, page 409  
12 lines 30–33, and page 411 lines 11–14 read

13 If the Fortran compiler provides TYPE(C\_PTR), then the following interface  
14 must be provided in the `mpi` module and should be provided in `mpif.h`  
15 through overloading, i.e., with the same routine name as the routine with  
16 INTEGER(KIND=MPI\_ADDRESS\_KIND) BASEPTR, but with a different specific  
17 procedure name:  
18

19 but should read (the underlining is only for showing the new word)

20  
21 If the Fortran compiler provides TYPE(C\_PTR), then the following generic  
22 interface must be provided in the `mpi` module and should be provided in  
23 `mpif.h` through overloading, i.e., with the same routine name as the rou-  
24 tine with INTEGER(KIND=MPI\_ADDRESS\_KIND) BASEPTR, but with a differ-  
25 ent specific procedure name:

- 26 • Section 8.2, page 340 lines 1–8, and Annex A.4.6, page 772, lines 38–46 read

27  
28 INTERFACE MPI\_ALLOC\_MEM  
29 SUBROUTINE MPI\_ALLOC\_MEM\_CPTR(SIZE, INFO, BASEPTR, IERROR)  
30 USE, INTRINSIC :: ISO\_C\_BINDING, ONLY : C\_PTR  
31 INTEGER :: INFO, IERROR  
32 INTEGER(KIND=MPI\_ADDRESS\_KIND) :: SIZE  
33 TYPE(C\_PTR) :: BASEPTR  
34 END SUBROUTINE  
35 END INTERFACE

36  
37 but should read

38  
39  
40 INTERFACE MPI\_ALLOC\_MEM  
41 SUBROUTINE MPI\_ALLOC\_MEM(SIZE, INFO, BASEPTR, IERROR)  
42 IMPORT :: MPI\_ADDRESS\_KIND  
43 INTEGER INFO, IERROR  
44 INTEGER(KIND=MPI\_ADDRESS\_KIND) SIZE, BASEPTR  
45 END SUBROUTINE  
46 SUBROUTINE MPI\_ALLOC\_MEM\_CPTR(SIZE, INFO, BASEPTR, IERROR)  
47 USE, INTRINSIC :: ISO\_C\_BINDING, ONLY : C\_PTR  
48 IMPORT :: MPI\_ADDRESS\_KIND

```

        INTEGER :: INFO, IERROR
        INTEGER(KIND=MPI_ADDRESS_KIND) :: SIZE
        TYPE(C_PTR) :: BASEPTR
    END SUBROUTINE
END INTERFACE

```

- Section 8.2, page 340 (MPI\_ALLOC\_MEM) lines 10–11 read

The linker name base of this overloaded function is MPI\_ALLOC\_MEM\_CPTR. The implied linker names are described in Section 17.1.5 on page 605.

but should read

The base procedure name of this overloaded function is MPI\_ALLOC\_MEM\_CPTR. The implied specific procedure names are described in Section 17.1.5 on page 605.

- Section 11.2.2, page 408 (MPI\_WIN\_ALLOCATE) line 2 reads

but with a different linker name:

but should read

but with a different specific procedure name:

- Section 11.2.2, page 408, lines 4–12, and Annex A.4.9, page 777, lines 31–40 read

```

INTERFACE MPI_WIN_ALLOCATE
    SUBROUTINE MPI_WIN_ALLOCATE_CPTR(SIZE, DISP_UNIT, INFO, COMM, BASEPTR, &
    WIN, IERROR)
        USE, INTRINSIC :: ISO_C_BINDING, ONLY : C_PTR
        INTEGER :: DISP_UNIT, INFO, COMM, WIN, IERROR
        INTEGER(KIND=MPI_ADDRESS_KIND) :: SIZE
        TYPE(C_PTR) :: BASEPTR
    END SUBROUTINE
END INTERFACE

```

but should read

```

INTERFACE MPI_WIN_ALLOCATE
    SUBROUTINE MPI_WIN_ALLOCATE(SIZE, DISP_UNIT, INFO, COMM, BASEPTR, &
    WIN, IERROR)
        IMPORT :: MPI_ADDRESS_KIND
        INTEGER DISP_UNIT, INFO, COMM, WIN, IERROR
        INTEGER(KIND=MPI_ADDRESS_KIND) SIZE, BASEPTR
    END SUBROUTINE
    SUBROUTINE MPI_WIN_ALLOCATE_CPTR(SIZE, DISP_UNIT, INFO, COMM, BASEPTR, &
    WIN, IERROR)
        USE, INTRINSIC :: ISO_C_BINDING, ONLY : C_PTR

```

```

1      IMPORT :: MPI_ADDRESS_KIND
2      INTEGER :: DISP_UNIT, INFO, COMM, WIN, IERROR
3      INTEGER(KIND=MPI_ADDRESS_KIND) :: SIZE
4      TYPE(C_PTR) :: BASEPTR
5      END SUBROUTINE
6  END INTERFACE

```

- Section 11.2.2, page 408 (MPI\_WIN\_ALLOCATE) lines 14–15 read

The linker name base of this overloaded function is MPI\_WIN\_ALLOCATE\_CPTR. The implied linker names are described in Section 17.1.5 on page 605.

but should read

The base procedure name of this overloaded function is MPI\_WIN\_ALLOCATE\_CPTR. The implied specific procedure names are described in Section 17.1.5 on page 605.

- Section 11.2.2, Page 408, lines 24–26 read:

The following info key is predefined:

same\_size — if set to true, then the implementation may assume that the argument size is identical on all processes.

That text should be deleted. Add the following text to page 406, after line 10:

same\_size — if set to true, then the implementation may assume that the argument size is identical on all processes.

- Section 11.2.3, page 409 (MPI\_WIN\_ALLOCATE\_SHARED) line 33 reads

but with a different linker name:

but should read

but with a different specific procedure name:

- Section 11.2.3, page 409, lines 35–43, and Annex A.4.9, page 777, line 46 through page 778, line 6 read

```

39  INTERFACE MPI_WIN_ALLOCATE_SHARED
40      SUBROUTINE MPI_WIN_ALLOCATE_SHARED_CPTR(SIZE, DISP_UNIT, INFO, COMM, &
41      BASEPTR, WIN, IERROR)
42          USE, INTRINSIC :: ISO_C_BINDING, ONLY : C_PTR
43          INTEGER :: DISP_UNIT, INFO, COMM, WIN, IERROR
44          INTEGER(KIND=MPI_ADDRESS_KIND) :: SIZE
45          TYPE(C_PTR) :: BASEPTR
46      END SUBROUTINE
47  END INTERFACE
48

```

but should read

```

INTERFACE MPI_WIN_ALLOCATE_SHARED
SUBROUTINE MPI_WIN_ALLOCATE_SHARED(SIZE, DISP_UNIT, INFO, COMM, &
BASEPTR, WIN, IERROR)
  IMPORT :: MPI_ADDRESS_KIND
  INTEGER DISP_UNIT, INFO, COMM, WIN, IERROR
  INTEGER(KIND=MPI_ADDRESS_KIND) SIZE, BASEPTR
END SUBROUTINE
SUBROUTINE MPI_WIN_ALLOCATE_SHARED_CPTR(SIZE, DISP_UNIT, INFO, COMM, &
BASEPTR, WIN, IERROR)
  USE, INTRINSIC :: ISO_C_BINDING, ONLY : C_PTR
  IMPORT :: MPI_ADDRESS_KIND
  INTEGER :: DISP_UNIT, INFO, COMM, WIN, IERROR
  INTEGER(KIND=MPI_ADDRESS_KIND) :: SIZE
  TYPE(C_PTR) :: BASEPTR
END SUBROUTINE
END INTERFACE

```

- Section 11.2.3, page 409 (MPI\_WIN\_ALLOCATE\_SHARED) lines 44–46 read

The linker name base of this overloaded function is  
MPI\_WIN\_ALLOCATE\_SHARED\_CPTR. The implied linker names are de-  
scribed in Section 17.1.5 on page 605.

but should read

The base procedure name of this overloaded function is  
MPI\_WIN\_ALLOCATE\_SHARED\_CPTR. The implied specific procedure names  
are described in Section 17.1.5 on page 605.

- Section 11.2.3, page 409, line 48: MPI\_WIN\_ALLOC should be changed to  
MPI\_WIN\_ALLOCATE.
- Section 11.2.3, page 411 (MPI\_WIN\_SHARED\_QUERY\_CPTR) line 14 reads

but with a different linker name:

but should read

but with a different specific procedure name:

- Section 11.2.3, page 411, lines 16–24, and Annex A.4.9, page 779, lines 12–20 read

```

INTERFACE MPI_WIN_SHARED_QUERY
SUBROUTINE MPI_WIN_SHARED_QUERY_CPTR(WIN, RANK, SIZE, DISP_UNIT, &
BASEPTR, IERROR)
  USE, INTRINSIC :: ISO_C_BINDING, ONLY : C_PTR
  INTEGER :: WIN, RANK, DISP_UNIT, IERROR
  INTEGER(KIND=MPI_ADDRESS_KIND) :: SIZE

```

```

1         TYPE(C_PTR) :: BASEPTR
2     END SUBROUTINE
3 END INTERFACE

```

but should read

```

7 INTERFACE MPI_WIN_SHARED_QUERY
8     SUBROUTINE MPI_WIN_SHARED_QUERY(WIN, RANK, SIZE, DISP_UNIT, &
9         BASEPTR, IERROR)
10        IMPORT :: MPI_ADDRESS_KIND
11        INTEGER WIN, RANK, DISP_UNIT, IERROR
12        INTEGER (KIND=MPI_ADDRESS_KIND) SIZE, BASEPTR
13    END SUBROUTINE
14    SUBROUTINE MPI_WIN_SHARED_QUERY_CPTR(WIN, RANK, SIZE, DISP_UNIT, &
15        BASEPTR, IERROR)
16        USE, INTRINSIC :: ISO_C_BINDING, ONLY : C_PTR
17        IMPORT :: MPI_ADDRESS_KIND
18        INTEGER :: WIN, RANK, DISP_UNIT, IERROR
19        INTEGER(KIND=MPI_ADDRESS_KIND) :: SIZE
20        TYPE(C_PTR) :: BASEPTR
21    END SUBROUTINE
22 END INTERFACE

```

- Section 11.2.3, page 411 (MPI\_WIN\_SHARED\_QUERY\_CPTR) lines 26–27 read

The linker name base of this overloaded function is MPI\_WIN\_SHARED\_QUERY\_CPTR. The implied linker names are described in Section 17.1.5 on page 605.

but should read

The base procedure name of this overloaded function is MPI\_WIN\_ALLOCATE\_CPTR. The implied specific procedure names are described in Section 17.1.5 on page 605.

- Section 11.3.4, page 428, lines 15–18 read

Accumulate `origin_count` elements of type `origin_datatype` from the origin buffer (`origin_addr`) to the buffer at offset `target_disp`, in the target window specified by `target_rank` and `win`, using the operation `op` and return in the result buffer `result_addr` the content of the target buffer before the accumulation.

but should say

Accumulate `origin_count` elements of type `origin_datatype` from the origin buffer (`origin_addr`) to the buffer at offset `target_disp`, in the target window specified by `target_rank` and `win`, using the operation `op` and return in the result buffer `result_addr` the content of the target buffer before the accumulation, specified by `target_disp`, `target_count`, and

`target_datatype`. The data transferred from origin to target must fit, without truncation, in the target buffer. Likewise, the data copied from target to origin must fit, without truncation, in the result buffer.

- Section 11.3.4, page 428, line 30, add

When `MPI_NO_OP` is specified as the operation, the `origin_addr`, `origin_count`, and `origin_datatype` arguments are ignored.

after

the origin and no operation is performed on the target buffer.

- Section 11.7.3, page 464, lines 16–20 read

While this ambiguity is unfortunate, it does not seem to affect many real codes. The MPI Forum decided not to decide which interpretation of the standard is the correct one, since the issue is very contentious, and a decision would have much impact on implementors but less impact on users.

but should be

While this ambiguity is unfortunate, the MPI Forum decided not to define which interpretation of the standard is the correct one, since the issue is contentious.

- Section 11.8, example 11.21, page 469, in line 32 change

```
double **baseptr;
```

to

```
double *baseptr;
```

and in line 36, change

```
MPI_COMM_WORLD, baseptr, &win);
```

to

```
MPI_COMM_WORLD, &baseptr, &win);
```

- Section 14.2.1, page 555 (Profiling interface) lines 38–40 read

For Fortran, the different support methods cause several linker names. Therefore, several profiling routines (with these linker names) are needed for each Fortran MPI routine, as described in Section 17.1.5 on page 605.

but should read

For Fortran, the different support methods cause several specific procedure names. Therefore, several profiling routines (with these specific procedure names) are needed for each Fortran MPI routine, as described in Section 17.1.5 on page 605.

- 1 • Section 14.2.7, page 560 (Profiling interface, Fortran support methods) lines 29–32  
2 read

3           The different Fortran support methods and possible options for the support  
4 of subarrays (depending on whether the compiler can support `TYPE(*)`,  
5 `DIMENSION(..)` choice buffers) imply different linker names for the same  
6 Fortran MPI routine. The rules and implications for the profiling interface  
7 are described in Section 17.1.5 on page 605.  
8

9 but should read

10           The different Fortran support methods and possible options for the support  
11 of subarrays (depending on whether the compiler can support `TYPE(*)`,  
12 `DIMENSION(..)` choice buffers) imply different specific procedure names for  
13 the same Fortran MPI routine. The rules and implications for the profiling  
14 interface are described in Section 17.1.5 on page 605.  
15

- 16 • Section 14.3, page 561, lines 33–36 read

17           Since the MPI tool information interface primarily focuses on tools and sup-  
18 port libraries, MPI implementations are only required to provide C bindings  
19 for functions introduced in this section.  
20

21 but should read

22           Since the MPI tool information interface primarily focuses on tools and sup-  
23 port libraries, MPI implementations are only required to provide C bindings  
24 for functions and constants introduced in this section.  
25  
26

- 27 • Section 17.1.1, page 598 (Fortran support, overview) lines 29–32 read

28           The Fortran interfaces of each MPI routine are shorthands. Section 17.1.5  
29 defines the corresponding full interface specification together with the used  
30 linker names and implications for the profiling interface.  
31

32 but should read

33           The Fortran interfaces of each MPI routine are shorthands. Section 17.1.5  
34 defines the corresponding full interface specification together with the spe-  
35 cific procedure names and implications for the profiling interface.  
36

- 37 • Section 17.1.2, page 599 (Fortran support through the `mpi_f08` module) lines 19–20  
38 read

39           Define all MPI handles with uniquely named handle types (instead of  
40 `INTEGER` handles, as in the `mpi` module).  
41

42 but should read

43           Define the derived type `MPI_Status`, and define all MPI handles with uniquely  
44 named handle types (instead of `INTEGER` handles, as in the `mpi` module).  
45  
46

- 47 • Section 17.1.2, page 601 (Fortran support through the `mpi_f08` module) lines 11–15  
48 read



The `INTERFACE` construct in combination with `BIND(C)` allows the implementation of the Fortran `mpi_f08` interface with a single set of portable wrapper routines written in C, which supports all desired features in the `mpi_f08` interface. TS 29113 also has a provision for `OPTIONAL` arguments in `BIND(C)` interfaces.

but should be removed.

- Section 17.1.3 (`mpi` module), page 601 lines 33–35 read

Provide explicit interfaces according to the Fortran routine interface specifications. This module therefore guarantees compile-time argument checking and allows positional and keyword-based argument lists.

but should read

Provide explicit interfaces according to the Fortran routine interface specifications. This module therefore guarantees compile-time argument checking and allows positional and keyword-based argument lists. If an implementation is paired with a compiler that either does not support `TYPE(*)`, `DIMENSION(..)` from TS 29113, or is otherwise unable to ignore the types of choice buffers, then the implementation must provide explicit interfaces only for MPI routines with no choice buffer arguments. See Section 17.1.6 on page 609 for more details.

- Both the last Advice to implementors in Section 17.1.4 (Fortran support through the `mpif.h` include file), page 604 line 29 through page 605 line 11, and the whole of Section 17.1.5 (Interface specification, linker names and the profiling interface), page 605 line 29 through page 609 line 31 are replaced with the following:

---

### 17.1.5 Interface Specifications, Procedure Names, and the Profiling Interface

The Fortran interface specification of each MPI routine specifies the routine name that must be called by the application program, and the names and types of the dummy arguments together with additional attributes. The Fortran standard allows a given Fortran interface to be implemented with several methods, e.g., within or outside of a module, with or without `BIND(C)`, or the buffers with or without TS 29113. Such implementation decisions imply different binary interfaces and different specific procedure names. The requirements for several implementation schemes together with the rules for the specific procedure names and its implications for the profiling interface are specified within this section, but not the implementation details.

*Rationale.* This section was introduced in MPI-3.0 on Sep. 21, 2012. The major goals for implementing the three Fortran support methods have been:

- Portable implementation of the wrappers from the MPI Fortran interfaces to the MPI routines in C.
- Binary backward compatible implementation path when switching `MPI_SUBARRAYS_SUPPORTED` from `.FALSE.` to `.TRUE.`

- 1       • The Fortran PMPI interface need not be backward compatible, but a method
- 2        must be included that a tools layer can use to examine the MPI library about
- 3        the specific procedure names and interfaces used.
- 4       • No performance drawbacks.
- 5       • Consistency between all three Fortran support methods.
- 6       • Consistent with Fortran 2008 + TS 29113.

8       The design expected that all dummy arguments in the MPI Fortran interfaces are  
 9       interoperable with C according to Fortran 2008 + TS 29113. This expectation was  
 10       not fulfilled. The LOGICAL arguments are not interoperable with C, mainly because  
 11       the internal representations for .FALSE. and .TRUE. are compiler dependent. The  
 12       provided interface was mainly based on BIND(C) interfaces and therefore inconsistent  
 13       with Fortran. To be consistent with Fortran, the BIND(C) had to be removed from  
 14       the callback procedure interfaces and the predefined callbacks, e.g.,  
 15       MPI\_COMM\_DUP\_FN. Non-BIND(C) procedures are also not interoperable with C,  
 16       and therefore the BIND(C) had to be removed from all routines with  
 17       PROCEDURE arguments, e.g., from MPI\_OP\_CREATE.

18       Therefore, this section was rewritten as an erratum to MPI-3.0. (*End of rationale.*)

19  
 20       A Fortran call to an MPI routine shall result in a call to a procedure with one of the  
 21       specific procedure names and calling conventions, as described in Table 1.1 on page 11.  
 22       Case is not significant in the names.

23       Note that for the deprecated routines in Section 15.1 on page 591, which are reported  
 24       only in Annex A.4, scheme 2A is utilized in the mpi module and mpif.h, and also in the  
 25       mpi\_f08 module.

26       To set MPI\_SUBARRAYS\_SUPPORTED to .TRUE. within a Fortran support method, it  
 27       is required that all non-blocking and split-collective routines with buffer arguments are  
 28       implemented according to 1B and 2B, i.e., with MPI\_Xxxx\_f08ts in the mpi\_f08 module,  
 29       and with MPI\_XXXX\_FTS in the mpi module and the mpif.h include file.

30       The mpi and mpi\_f08 modules and the mpif.h include file will each correspond to  
 31       exactly one implementation scheme from Table 1.1 on page 11. However, the MPI library  
 32       may contain multiple implementation schemes from Table 1.1.

33  
 34       *Advice to implementors.* This may be desirable for backwards binary compatibility  
 35       in the scope of a single MPI implementation, for example. (*End of advice to imple-*  
 36       *mentors.*)

37  
 38       *Rationale.* After a compiler provides the facilities from TS 29113, i.e., TYPE(\*),  
 39       DIMENSION(. .), it is possible to change the bindings within a Fortran support method  
 40       to support subarrays without recompiling the complete application provided that the  
 41       previous interfaces with their specific procedure names are still included in the li-  
 42       brary. Of course, only recompiled routines can benefit from the added facilities.  
 43       There is no binary compatibility conflict because each interface uses its own spe-  
 44       cific procedure names and all interfaces use the same constants (except the value of  
 45       MPI\_SUBARRAYS\_SUPPORTED and MPI\_ASYNC\_PROTECTS\_NONBLOCKING) and type  
 46       definitions. After a compiler also ensures that buffer arguments of nonblocking MPI  
 47       operations can be protected through the ASYNCHRONOUS attribute, and the proce-  
 48       dure declarations in the mpi\_f08 and mpi module and the mpif.h include file declare

No.	Specific procedure name	Calling convention
1A	MPI_Isend_f08	Fortran interface and arguments, as in Annex A.3, except that in routines with a choice buffer dummy argument, this dummy argument is implemented with non-standard extensions like <code>!\$PRAGMA IGNORE_TKR</code> , which provides a call-by-reference argument without type, kind, and dimension checking.
1B	MPI_Isend_f08ts	Fortran interface and arguments, as in Annex A.3, but only for routines with one or more choice buffer dummy arguments; these dummy arguments are implemented with <code>TYPE(*)</code> , <code>DIMENSION(..)</code> .
2A	MPI_ISEND	Fortran interface and arguments, as in Annex A.4, except that in routines with a choice buffer dummy argument, this dummy argument is implemented with non-standard extensions like <code>!\$PRAGMA IGNORE_TKR</code> , which provides a call-by-reference argument without type, kind, and dimension checking.
2B	MPI_ISEND_FTS	Fortran interface and arguments, as in Annex A.4, but only for routines with one or more choice buffer dummy arguments; these dummy arguments are implemented with <code>TYPE(*)</code> , <code>DIMENSION(..)</code> .

Table 1.1: Specific Fortran procedure names and related calling conventions. `MPI_ISEND` is used as an example. For routines without choice buffers, only 1A and 2A apply.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48

1 choice buffers with the `ASYNCHRONOUS` attribute, then the value of  
 2 `MPI_ASYNC_PROTECTS_NONBLOCKING` can be switched to `.TRUE.` in the module def-  
 3 inition and include file. (*End of rationale.*)

4  
 5 *Advice to users.* Partial recompilation of user applications when upgrading MPI  
 6 implementations is a highly complex and subtle topic. Users are strongly advised to  
 7 consult their MPI implementation’s documentation to see exactly what is — and what  
 8 is not — supported. (*End of advice to users.*)

9  
 10 Within the `mpi_f08` and `mpi` modules and `mpif.h`, for all MPI procedures, a second  
 11 procedure with the same calling conventions shall be supplied, except that the name is  
 12 modified by prefixing with the letter “P”, e.g., `PMPI_Isend`. The specific procedure names  
 13 for these `PMPI_Xxxx` procedures must be different from the specific procedure names for  
 14 the `MPI_Xxxx` procedures and are not specified by this standard.

15 A user-written or middleware profiling routine should provide the same specific For-  
 16 tran procedure names and calling conventions, and therefore can interpose itself as the  
 17 MPI library routine. The profiling routine can internally call the matching `PMPI` routine  
 18 with any of its existing bindings, except for routines that have callback routine dummy  
 19 arguments, choice buffer arguments, or that are attribute caching routines (  
 20 `MPI_{COMM|WIN|TYPE}_{SET|GET}_ATTR`). In this case, the profiling software should  
 21 invoke the corresponding `PMPI` routine using the same Fortran support method as used in  
 22 the calling application program, because the C, `mpi_f08` and `mpi` callback prototypes are  
 23 different or the meaning of the choice buffer or `attribute_val` arguments are different.

24  
 25 *Advice to users.* Although for each support method and MPI routine (e.g.,  
 26 `MPI_ISEND` in `mpi_f08`), multiple routines may need to be provided to intercept  
 27 the specific procedures in the MPI library (e.g., `MPI_Isend_f08` and `MPI_Isend_f08ts`),  
 28 each profiling routine itself uses only one support method (e.g., `mpi_f08`) and calls  
 29 the real MPI routine through the one `PMPI` routine defined in this support method  
 30 (i.e., `PMPI_Isend` in this example). (*End of advice to users.*)

31 *Advice to implementors.* If all of the following conditions are fulfilled:

- 32
- 33 ● the handles in the `mpi_f08` module occupy one Fortran numerical storage unit
- 34 (same as an `INTEGER` handle),
- 35 ● the internal argument passing mechanism used to pass an actual `ierror` argument
- 36 to a non-optional `ierror` dummy argument is binary compatible to passing an
- 37 actual `ierror` argument to an `ierror` dummy argument that is declared as `OPTIONAL`,
- 38 ● the internal argument passing mechanism for `ASYNCHRONOUS` and non-
- 39 `ASYNCHRONOUS` arguments is the same,
- 40 ● the internal routine call mechanism is the same for the Fortran and the C com-
- 41 pilers for which the MPI library is compiled,
- 42 ● the compiler does not provide TS 29113,
- 43

44  
 45 then the implementor may use the same internal routine implementations for all For-  
 46 tran support methods but with several different specific procedure names. If the  
 47 accompanying Fortran compiler supports TS 29113, then the new routines are needed  
 48 only for routines with choice buffer arguments. (*End of advice to implementors.*)

*Advice to implementors.* In the Fortran support method `mpif.h`, compile-time argument checking can be also implemented for all routines. For `mpif.h`, the argument names are not specified through the MPI standard, i.e., only positional argument lists are defined, and not key-word based lists. Due to the rule that `mpif.h` must be valid for fixed and free source form, the subroutine declaration is restricted to one line with 72 characters. To keep the argument lists short, each argument name can be shortened to a minimum of one character. With this, the two longest subroutine declaration statements are

```

SUBROUTINE PMPI_Dist_graph_create_adjacent(a,b,c,d,e,f,g,h,i,j,k)
SUBROUTINE PMPI_Rget_accumulate(a,b,c,d,e,f,g,h,i,j,k,l,m,n)

```

with 71 and 66 characters. With buffers implemented with TS 29113, the specific procedure names have an additional postfix. The longest of such interface definitions is

```

INTERFACE PMPI_Rget_accumulate
SUBROUTINE PMPI_Rget_accumulate_fts(a,b,c,d,e,f,g,h,i,j,k,l,m,n)

```

with 70 characters. In principle, continuation lines would be possible in `mpif.h` (spaces in columns 73–131, & in column 132, and in column 6 of the continuation line) but this would not be valid if the source line length is extended with a compiler flag to 132 characters. Column 133 is also not available for the continuation character because lines longer than 132 characters are invalid with some compilers by default.

The longest specific procedure names are `PMPI_Dist_graph_create_adjacent_f08` and `PMPI_File_write_ordered_begin_f08ts` both with 35 characters in the `mpi_f08` module. For example, the interface specifications together with the specific procedure names can be implemented with

```

MODULE mpi_f08
  TYPE, BIND(C) :: MPI_Comm
  INTEGER :: MPI_VAL
  END TYPE MPI_Comm
  ...
  INTERFACE MPI_Comm_rank ! (as defined in Chapter 6)
    SUBROUTINE MPI_Comm_rank_f08(comm, rank, ierror)
      IMPORT :: MPI_Comm
      TYPE(MPI_Comm), INTENT(IN) :: comm
      INTEGER, INTENT(OUT) :: rank
      INTEGER, OPTIONAL, INTENT(OUT) :: ierror
    END SUBROUTINE
  END INTERFACE
END MODULE mpi_f08

MODULE mpi
  INTERFACE MPI_Comm_rank ! (as defined in Chapter 6)
    SUBROUTINE MPI_Comm_rank(comm, rank, ierror)
      INTEGER, INTENT(IN) :: comm ! The INTENT may be added although
      INTEGER, INTENT(OUT) :: rank ! it is not defined in the
      INTEGER, INTENT(OUT) :: ierror ! official routine definition.
    END SUBROUTINE
  END INTERFACE

```

```

1      END SUBROUTINE
2      END INTERFACE
3  END MODULE mpi

```

And if interfaces are provided in `mpif.h`, they might look like this (outside of any module and in fixed source format):

```

7      !23456789012345678901234567890123456789012345678901234567890123456789012
8      INTERFACE MPI_Comm_rank ! (as defined in Chapter 6)
9          SUBROUTINE MPI_Comm_rank(comm, rank, ierror)
10             INTEGER, INTENT(IN) :: comm ! The argument names may be
11             INTEGER, INTENT(OUT) :: rank ! shortened so that the
12             INTEGER, INTENT(OUT) :: ierror ! subroutine line fits to the
13             END SUBROUTINE ! maximum of 72 characters.
14          END INTERFACE

```

(*End of advice to implementors.*)

*Advice to users.* The following is an example of how a user-written or middleware profiling routine can be implemented:

```

19
20 SUBROUTINE MPI_Isend_f08ts(buf, count, datatype, dest, tag, comm, request, ierror)
21     USE :: mpi_f08, my_noname => MPI_Isend_f08ts
22     TYPE(*), DIMENSION(..), ASYNCHRONOUS :: buf
23     INTEGER, INTENT(IN) :: count, dest, tag
24     TYPE(MPI_Datatype), INTENT(IN) :: datatype
25     TYPE(MPI_Comm), INTENT(IN) :: comm
26     TYPE(MPI_Request), INTENT(OUT) :: request
27     INTEGER, OPTIONAL, INTENT(OUT) :: ierror
28     ! ... some code for the begin of profiling
29     call PMPI_Isend (buf, count, datatype, dest, tag, comm, request, ierror)
30     ! ... some code for the end of profiling
31 END SUBROUTINE MPI_Isend_f08ts

```

Note that this routine is used to intercept the existing specific procedure name `MPI_Isend_f08ts` in the MPI library. This routine must not be part of a module. This routine itself calls `PMPI_Isend`. The `USE` of the `mpi_f08` module is needed for definitions of handle types and the interface for `PMPI_Isend`. However, this module also contains an interface definition for the specific procedure name `MPI_Isend_f08ts` that conflicts with the definition of this profiling routine (i.e., the name is doubly defined). Therefore, the `USE` here specifically excludes the interface from the module by renaming the unused routine name in the `mpi_f08` module into “`my_noname`” in the scope of this routine. (*End of advice to users.*)

*Advice to users.* The `PMPI` interface allows intercepting MPI routines. For example, an additional `MPI_ISEND` profiling wrapper can be provided that is called by the application and internally calls `PMPI_ISEND`. There are two typical use cases: a profiling layer that is developed independently from the application and the MPI library, and profiling routines that are part of the application and have access to the application data. With MPI-3.0, new Fortran interfaces and implementation schemes were introduced that have several implications on how Fortran MPI routines are internally

implemented and optimized. For profiling layers, these schemes imply that several internal interfaces with different specific procedure names may need to be intercepted, as shown in the example code above. Therefore, for wrapper routines that are part of a Fortran application, it may be more convenient to make the name shift within the application, i.e., to substitute the call to the MPI routine (e.g., `MPI_ISEND`) by a call to a user-written profiling wrapper with a new name (e.g., `X_MPI_ISEND`) and to call the Fortran `MPI_ISEND` from this wrapper, instead of using the PMPI interface. (*End of advice to users.*)

- 
- Section 17.1.6, page 610 (MPI for different Fortran standard versions) line 27 reads
 

The routines are not `BIND(C)`.

but should be removed.
  - Section 17.1.6, page 610 (MPI for different Fortran standard versions) line 33 reads
 

The linker names are specified in Section 17.1.5 on page 605.

but should read

The specific procedure names are specified in Section 17.1.5 on page 605.
  - Section 17.1.6, page 611 (MPI for different Fortran standard versions) line 21 reads
 

`BIND(C, NAME='...')` interfaces.

but should be removed.
  - After Section 17.1.6, page 611 (MPI for different Fortran standard versions) line 26, which reads
 

arguments.

the following list item should be added:

The ability to overload the operators `.EQ.` and `.NE.` to allow the comparison of derived types (used in MPI-3.0 for MPI handles).
  - Section 17.1.6, page 611 (MPI for different Fortran standard versions) line 43 reads
 

The routines are not `BIND(C)`.

but should be removed.
  - Section 17.1.6, page 611 (MPI for different Fortran standard versions) line 47 reads
 

The linker names are specified in Section 17.1.5 on page 605.

but should read

The specific procedure names are specified in Section 17.1.5 on page 605.
  - Section 17.1.6, page 612 (MPI for different Fortran standard versions) lines 22–24 read

- 1           – OPTIONAL dummy arguments are allowed in combination with BIND(C)
- 2            interfaces.
- 3           – CHARACTER(LEN=\*) dummy arguments are allowed in combination with
- 4            BIND(C) interfaces.

5  
6       but should be removed.

- 7       • Section 17.1.7, page 614 (Requirements on Fortran compilers) lines 25–47 read

8  
9       All of these rules are valid independently of whether the MPI routine in-  
10       terfaces in the `mpi_f08` and `mpi` modules are internally defined with an  
11       INTERFACE or CONTAINS construct, and with or without BIND(C), and also  
12       if `mpif.h` uses explicit interfaces.

13           *Advice to implementors.*     Some of these rules are already part of  
14       the Fortran 2003 standard if the MPI interfaces are defined without  
15       BIND(C). Additional compiler support may be necessary if BIND(C) is  
16       used. Some of these additional requirements are defined in the Fortran  
17       TS 29113 [41]. Some of these requirements for MPI-3.0 are beyond the  
18       scope of TS 29113. (*End of advice to implementors.*)

19       Further requirements apply if the MPI library internally uses  
20       BIND(C) routine interfaces (i.e., for a full implementation of `mpi_f08`):

- 21           – Non-buffer arguments are INTEGER, INTEGER(KIND=...),
- 22            CHARACTER(LEN=\*), LOGICAL, and BIND(C) derived types (handles and
- 23            status in `mpi_f08`), variables and arrays; function results are DOUBLE
- 24            PRECISION. All these types must be valid as dummy arguments in the
- 25            BIND(C) MPI routine interfaces. When compiling an MPI application,
- 26            the compiler should not issue warnings indicating that these types may
- 27            not be interoperable with an existing type in C. Some of these types
- 28            are already valid in BIND(C) interfaces since Fortran 2003, some may
- 29            be valid based on TS 29113 (e.g., CHARACTER\*(\*)).
- 30           – OPTIONAL dummy arguments are also valid within
- 31            BIND(C) interfaces. This requirement is fulfilled if TS 29113 is fully
- 32            supported by the compiler.

33  
34       but should read

35  
36       All of these rules are valid for the `mpi_f08` and `mpi` modules and indepen-  
37       dently of whether `mpif.h` uses explicit interfaces.

38           *Advice to implementors.*     Some of these rules are already part of the  
39       Fortran 2003 standard, some of these requirements require the Fortran  
40       TS 29113 [41], and some of these requirements for MPI-3.0 are beyond  
41       the scope of TS 29113. (*End of advice to implementors.*)

- 42  
43       • Annex A.1, page 674, line 31 reads

44           Fortran Type: INTEGER

45  
46       but should be deleted.

- 47  
48       • Annex A.1, page 675, line 4 reads



- Fortran Type: INTEGER 1
- but should be deleted. 2
- 3
- Annex A.1, page 675, line 21 reads 4
    - Fortran Type: INTEGER 5
    - but should be deleted. 6
  - Annex A.1, page 676, line 4 reads 7
    - Fortran Type: INTEGER 8
    - but should be deleted. 9
  - Annex A.1.2, page 677 (Handle types in the `mpi_f08` and `mpi` modules) line 10 reads 10
    - TYPE(MPI\_Info) 11
    - but should read 12
    - TYPE(MPI\_Info) 13
    - TYPE(MPI\_Message) 14
  - Annex A.1.5 Info Keys, page 683, lines 17 and later, add (maintaining the sorted order): 15
    - accumulate\_ordering 16
    - accumulate\_ops 17
    - same\_size 18
    - alloc\_shared\_noncontig 19
  - Annex A.1.6 Info Values, page 684, beginning at line 1, add (maintaining the sorted order): 20
    - rar 21
    - raw 22
    - same\_op 23
    - same\_op\_no\_op 24
    - war 25
    - waw 26
  - Annex A.2.11, page 700, line 46 reads 27
    - int MPI\_File\_close(MPI\_File \*fh) 28
    - but should read (add MPI\_CONVERSION\_FN\_NULL before) 29
    - int MPI\_CONVERSION\_FN\_NULL(void \*userbuf, MPI\_Datatype datatype, int 30
    - count, void \*filebuf, MPI\_Offset position, void \*extra\_state) 31
    - int MPI\_File\_close(MPI\_File \*fh) 32

- Annex A.3.11, page 747, line 36 reads

```
MPI_File_close(fh, ierror) BIND(C)
```

but should read (add MPI\_CONVERSION\_FN\_NULL before, but without BIND(C))

```
SUBROUTINE MPI_CONVERSION_FN_NULL(userbuf, datatype, count, filebuf,
position, extra_state, ierror)
```

```
    USE, INTRINSIC :: ISO_C_BINDING, ONLY : C_PTR
```

```
    TYPE(C_PTR), VALUE :: userbuf, filebuf
```

```
    TYPE(MPI_Datatype) :: datatype
```

```
    INTEGER :: count, ierror
```

```
    INTEGER(KIND=MPI_OFFSET_KIND) :: position
```

```
    INTEGER(KIND=MPI_ADDRESS_KIND) :: extra_state
```

```
MPI_File_close(fh, ierror)
```

- Annex A.4.11, page 780, line 22 reads

```
MPI_FILE_CLOSE(FH, IERROR)
```

but should read (add MPI\_CONVERSION\_FN\_NULL before)

```
SUBROUTINE MPI_CONVERSION_FN_NULL(USERBUF, DATATYPE, COUNT, FILEBUF,
POSITION, EXTRA_STATE, IERROR)
```

```
    <TYPE> USERBUF(*), FILEBUF(*)
```

```
    INTEGER COUNT, DATATYPE, IERROR
```

```
    INTEGER(KIND=MPI_OFFSET_KIND) POSITION
```

```
    INTEGER(KIND=MPI_ADDRESS_KIND) EXTRA_STATE
```

```
MPI_FILE_CLOSE(FH, IERROR)
```

- Annex A.3.4, page 724 lines 15–40 read

```
MPI_COMM_DUP_FN(oldcomm, comm_keyval, extra_state, attribute_val_in,
attribute_val_out, flag, ierror) BIND(C)
```

```
    TYPE(MPI_Comm), INTENT(IN) :: oldcomm
```

```
    INTEGER, INTENT(IN) :: comm_keyval
```

```
    INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(IN) :: extra_state,
```

```
    attribute_val_in
```

```
    INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(OUT) :: attribute_val_out
```

```
    LOGICAL, INTENT(OUT) :: flag
```

```
    INTEGER, INTENT(OUT) :: ierror
```

```
MPI_COMM_NULL_COPY_FN(oldcomm, comm_keyval, extra_state,
attribute_val_in, attribute_val_out, flag, ierror) BIND(C)
```

```
    TYPE(MPI_Comm), INTENT(IN) :: oldcomm
```

```
    INTEGER, INTENT(IN) :: comm_keyval
```

```
    INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(IN) :: extra_state,
```

```
    attribute_val_in
```

```
    INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(OUT) :: attribute_val_out
```

```
    LOGICAL, INTENT(OUT) :: flag
```

```

    INTEGER, INTENT(OUT) :: ierror
1
2
MPI_COMM_NULL_DELETE_FN(comm, comm_keyval, attribute_val, extra_state,
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48

```

but should read (without all INTENT information and BIND(C))

```

MPI_COMM_DUP_FN(oldcomm, comm_keyval, extra_state, attribute_val_in,
attribute_val_out, flag, ierror)
    TYPE(MPI_Comm) :: oldcomm
    INTEGER :: comm_keyval
    INTEGER(KIND=MPI_ADDRESS_KIND) :: extra_state, attribute_val_in
    INTEGER(KIND=MPI_ADDRESS_KIND) :: attribute_val_out
    LOGICAL :: flag
    INTEGER :: ierror

MPI_COMM_NULL_COPY_FN(oldcomm, comm_keyval, extra_state,
attribute_val_in, attribute_val_out, flag, ierror)
    TYPE(MPI_Comm) :: oldcomm
    INTEGER :: comm_keyval
    INTEGER(KIND=MPI_ADDRESS_KIND) :: extra_state, attribute_val_in
    INTEGER(KIND=MPI_ADDRESS_KIND) :: attribute_val_out
    LOGICAL :: flag
    INTEGER :: ierror

MPI_COMM_NULL_DELETE_FN(comm, comm_keyval, attribute_val, extra_state,
ierror)
    TYPE(MPI_Comm) :: comm
    INTEGER :: comm_keyval
    INTEGER(KIND=MPI_ADDRESS_KIND) :: attribute_val, extra_state
    INTEGER :: ierror

```

- Annex A.3.4, page 728 line 44 through page 729 line 22 reads

```

MPI_TYPE_DUP_FN(oldtype, type_keyval, extra_state, attribute_val_in,
attribute_val_out, flag, ierror) BIND(C)
    TYPE(MPI_Datatype), INTENT(IN) :: oldtype
    INTEGER, INTENT(IN) :: type_keyval
    INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(IN) :: extra_state,
attribute_val_in
    INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(OUT) :: attribute_val_out
    LOGICAL, INTENT(OUT) :: flag
    INTEGER, INTENT(OUT) :: ierror

MPI_TYPE_NULL_COPY_FN(oldtype, type_keyval, extra_state,

```

```

1 attribute_val_in, attribute_val_out, flag, ierror) BIND(C)
2     TYPE(MPI_Datatype), INTENT(IN) :: oldtype
3     INTEGER, INTENT(IN) :: type_keyval
4     INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(IN) :: extra_state,
5     attribute_val_in
6     INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(OUT) :: attribute_val_out
7     LOGICAL, INTENT(OUT) :: flag
8     INTEGER, INTENT(OUT) :: ierror

```

```

9
10 MPI_TYPE_NULL_DELETE_FN(datatype, type_keyval, attribute_val,
11 extra_state, ierror) BIND(C)
12     TYPE(MPI_Datatype), INTENT(IN) :: datatype
13     INTEGER, INTENT(IN) :: type_keyval
14     INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(IN) :: attribute_val,
15     extra_state
16     INTEGER, INTENT(OUT) :: ierror

```

17 but should read (without all INTENT information and BIND(C))

```

18
19 MPI_TYPE_DUP_FN(oldtype, type_keyval, extra_state, attribute_val_in,
20 attribute_val_out, flag, ierror)
21     TYPE(MPI_Datatype) :: oldtype
22     INTEGER :: type_keyval
23     INTEGER(KIND=MPI_ADDRESS_KIND) :: extra_state, attribute_val_in
24     INTEGER(KIND=MPI_ADDRESS_KIND) :: attribute_val_out
25     LOGICAL :: flag
26     INTEGER :: ierror

```

```

27
28 MPI_TYPE_NULL_COPY_FN(oldtype, type_keyval, extra_state,
29 attribute_val_in, attribute_val_out, flag, ierror)
30     TYPE(MPI_Datatype) :: oldtype
31     INTEGER :: type_keyval
32     INTEGER(KIND=MPI_ADDRESS_KIND) :: extra_state, attribute_val_in
33     INTEGER(KIND=MPI_ADDRESS_KIND) :: attribute_val_out
34     LOGICAL :: flag
35     INTEGER :: ierror

```

```

36
37 MPI_TYPE_NULL_DELETE_FN(datatype, type_keyval, attribute_val,
38 extra_state, ierror)
39     TYPE(MPI_Datatype) :: datatype
40     INTEGER :: type_keyval
41     INTEGER(KIND=MPI_ADDRESS_KIND) :: attribute_val, extra_state
42     INTEGER :: ierror

```

43

- 44 • Annex A.3.4, page 730 lines 15–38 read

```

45 MPI_WIN_DUP_FN(oldwin, win_keyval, extra_state, attribute_val_in,
46 attribute_val_out, flag, ierror) BIND(C)
47     INTEGER, INTENT(IN) :: oldwin, win_keyval
48

```

```

    INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(IN) ::  extra_state,      1
    attribute_val_in                                           2
    INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(OUT) ::  attribute_val_out  3
    LOGICAL, INTENT(OUT) ::  flag                               4
    INTEGER, INTENT(OUT) ::  ierror                             5
                                                                6
MPI_WIN_NULL_COPY_FN(oldwin, win_keyval, extra_state,      7
attribute_val_in, attribute_val_out, flag, ierror) BIND(C)  8
    INTEGER, INTENT(IN) ::  oldwin, win_keyval                 9
    INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(IN) ::  extra_state, 10
    attribute_val_in                                           11
    INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(OUT) ::  attribute_val_out 12
    LOGICAL, INTENT(OUT) ::  flag                               13
    INTEGER, INTENT(OUT) ::  ierror                             14
                                                                15
MPI_WIN_NULL_DELETE_FN(win, win_keyval, attribute_val, extra_state, 16
ierror) BIND(C)                                             17
    TYPE(MPI_Win), INTENT(IN) ::  win                          18
    INTEGER, INTENT(IN) ::  win_keyval                         19
    INTEGER(KIND=MPI_ADDRESS_KIND), INTENT(IN) ::  attribute_val, 20
    extra_state                                               21
    INTEGER, INTENT(OUT) ::  ierror                             22
                                                                23
but should read (without all INTENT information, BIND(C), and oldwin as 24
TYPE(MPI_Win))                                             25
MPI_WIN_DUP_FN(oldwin, win_keyval, extra_state, attribute_val_in, 26
attribute_val_out, flag, ierror)                             27
    TYPE(MPI_Win) ::  oldwin                                  28
    INTEGER ::  win_keyval                                    29
    INTEGER(KIND=MPI_ADDRESS_KIND) ::  extra_state, attribute_val_in 30
    INTEGER(KIND=MPI_ADDRESS_KIND) ::  attribute_val_out      31
    LOGICAL ::  flag                                         32
    INTEGER ::  ierror                                        33
                                                                34
MPI_WIN_NULL_COPY_FN(oldwin, win_keyval, extra_state,      35
attribute_val_in, attribute_val_out, flag, ierror)          36
    TYPE(MPI_Win) ::  oldwin                                  37
    INTEGER ::  win_keyval                                    38
    INTEGER(KIND=MPI_ADDRESS_KIND) ::  extra_state, attribute_val_in 39
    INTEGER(KIND=MPI_ADDRESS_KIND) ::  attribute_val_out      40
    LOGICAL ::  flag                                         41
    INTEGER ::  ierror                                        42
                                                                43
MPI_WIN_NULL_DELETE_FN(win, win_keyval, attribute_val, extra_state, 44
ierror)                                                     45
    TYPE(MPI_Win) ::  win                                     46
    INTEGER ::  win_keyval                                    47
    INTEGER(KIND=MPI_ADDRESS_KIND) ::  attribute_val, extra_state 48

```

```
1      INTEGER :: ierror
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
```